

YT-C5003



- High Performance TI DM36X CPU.
- Support IR-CUT filter switch to achieve day and night monitoring
- Support local BNC output
- H.264 High profile compression, achieve low bit-rate, high definition image quality
- Support dual stream
- Support mobile monitor (iPhone, Windows Mobile, BlackBerry, Symbian, Android)
- Support Auto-iris and electronic shutter, adjust for different surveillance environment
- Provide web, CMS, center manage software (MYEYE), and SDK for development
- Support connection with HVR/NVR&Onvif
- Cloud function: No need router mapping, No need to register and config DDNS, No need to be professional at network and PC.

Model	YT-C5003 House Hold Cube IPC
Camera	
Image Sensor	1/5" CMOS Sensor
Low Illumination	Color 0.1Lux @(F1.2,AGC ON),0 LUX with IR
BW 0.01 Lux @ (F1.2,AGC ON),0 LUX with IR	
Electronic shutter	1/50(1/60)S- 1/100,000 S
Lens	4mm @F2.0
Lens Mount	M12
Day/Night	Support IR-CUT
Video Compression	H.264 HighProfile, JPEG snapshot
Bite Rate	32 Kbps~2Mbps
Image	
Max.Image Resolution	1280*720
Frame Rate	50Hz:25fps (640*480), 22fps (1280*720)
Mage Setting	

Network	
Storage	Network storage Support TF card
Intelligent Alarm	Motion detect, video loss, network disconnection..
Protocol	TCP/IP,HTTP,DHCP,DNS,DDNS,PPPoE,SMTP,NTP(HTTPS,SIP,802.1x,Ipv6 optional)
Protocol	
Basic	Anti-flicker,dual stream,heartbeat,password protection
Interface	
Net Interface	1 * RJ45 10M/100M
Video output	1Vp-p Composite Output(75Ω/BNC)
Audio Input	1ch Microphone
Audio Output	1ch,3.5mm,Jack port
General	
Operating Condition	-10°C~60°C, Humidity 90% or less(non-condensing)
Power supply	DC12V±10%
IR Distance	25m
Dimension	110mm*70mm*33mm
Weight	185g